

REV OV R9 51.2V 200Ah 10.2kWh



KEY FEATURES

- **LiFePO₄** chemistry is considered very safe even if fully charged.
- Reliability – battery designed to operate in almost any environment.
- Durability – life expectancy exceeding 10 years at 25°C.
- Supports parallel bus bar connection.
- External BMS.
- Manufacturing plants comply with the legislation in each country and with international quality standards ISO9001 and Qs9000.
- Residential, Business, Factory, Data Centres or Telecoms Base Station backup.
- Solar, Wind or Hybrid Storage.
- Reduce Peak Usage Charges from the Grid.

WARRANTY

REV OV Batteries (PTY) LTD: 10 years or 3 500 cycles at 1 cycle per day.

DOD When used properly every day the R9 can be safely discharged to 100% of its rated 200Ah capacity. Battery life is shortened if it is discharged beyond its rated Ah capacity.

CODE: SYS – 2LiFe – R9 – 200 – 10.2

FREEDOM FROM DEPENDENCE

WWW.REV OV.CO.ZA

The REV OV 2nd LiFePO₄ R9 is an energy storage Lithium Iron Phosphate battery using a superior 16 cell configuration, made up of automotive grade cells, which is designed to withstand harsher conditions, extreme temperatures and with a higher energy density. A lithium iron battery has a **service lifespan of 15 to 25 years**, depending on how it is used.

A REV OV 2nd LiFe R9 battery spends its first life powering 1800 cycles in electrical vehicles (EV). Its 2nd LiFe as a repurposed battery is perfect for static energy storage solutions, at a greatly reduced cost. The system offers unrivalled value in terms of life cycle cost and capital outlay.

REV OV 2nd LiFe batteries are environmentally responsible, reducing electronic waste and repurposing important materials. The R9 battery is designed with a cycle-life of over 7000+ cycles, making them ideal for residential, commercial and industrial applications.



BMS FUNCTION

- Cell and battery voltage detection.
- RS485 communication interface.
- Battery charge and discharge control (MOSFET).
- Cell, ambient and MOSFET temperature detection.
- Display of the Battery capacity and number of cycles.
- Cells balancing – Equalization of single cells intelligently.
- Watchdog protection for circuits to ensure safe operation.

SPECIFICATIONS

Charge Voltage	Float Charge	54.5V
	Boost / Absorption Charge	55.5V
Recommended Charge Current		60A
Max Output Power		10.24Wh
Recharge Time		4hrs
Nominal Voltage		51.2V
Capacity		200Ah
BMS Size: Length x Width x Height		483mm x 280mm x 42mm
BMS Weight:		3.6kg
Battery Size: Length x Width x Height		520mm x 442mm x 170mm
Battery Weight:		53kg

Each BMS must have a dedicated fuse (125A) to protect the system

NOMINAL SPECIFICATIONS

	Matched Pair
Nominal Voltage	51.2 (25.6V x 2)
Capacity (C/2)	200Ah
Energy (C/2)	10.24Wh
Maintenance	Charge the battery every 6 months when in storage

OPERATING CONDITIONS

Designed Cycle Life + 25°C	7000+ cycles
Operating Temperature	
Charge:	Zero / 45°C
Discharge:	-20°C / 60°C
Transport Regulation Compliance	UN3480
Storage Temperature	Short Term Storage: -10°C~+45°C (<3 months, SOC: 20%~60%) Long Term Storage: -10°C~+40°C
EMC Standard Compliance	EN 61000 chapter 4.2, 4.3, 4.5, 4.6/EN55022
Certificate	TUV SUD/CE UL1642/ UN38.3
Protection Class	IP20

